

Steel Wrangler 15 Ton

When you're buying for the big load and the long haul, the Wrangler 15-ton carrier is a good investment. It delivers 30,000 lbs of payload capacity, impressive load angles, and years of reliable use. The Wrangler carrier is available in 24', 26' and 28' decks with or without steel removable rails.

Standard Equipment

Body

- Dual Lighted Control Stations with Durable Polycarbonate Placards, Polyethylene Hoods and Polished Aluminum Handles
- Reinforced Rigid Tubular Steel Subframe with No Lube Pivot Joints
- No Lube High Performance Replaceable Slide Pad System
- Flexible Nylon Hose / Cable Carrier Tracking System
- Adjustable Tilt Stabilizer Bumpers

Deck

- 36 KSI, 3/16" Diamond Steel Decking
- W8 x 21 lb/ft Steel Main Deck Beams
- Reinforced Low-Profile Tapered Approach Tip
- Steel Mini-I Beam Crossmembers on 8" Centers
- Steel Angle Flush Style Rubrails with Stake Pockets
- Two Chain and Binder Trays Abreast of Winch
- Heavy Duty Deck Lock / Hold Down System

Headboard

- Deluxe Bolt-On Steel Headboard with Screen

Hydraulics

- Dual Hydraulic Counterbalance Locking Valve on Deck Tilt Function
- Abrasion Resistant / Thermal Resistant Hydraulic Hoses
- Hydraulic Reservoir with Integrated Oil Level / Temperature Gauge and Magnetic Clean-Out Provision
- Hydraulic Supply and Return Filtration
- Chrome Plated Cylinder Rods
- System Overload Protection

Lighting

- FMVSS 108 Light Group Utilizing Weather Resistant Harnesses and

Connectors

Misc.

- Back-Up Alarm
- Mud Flaps

Paint

- Deck and Subframe Painted Black

PTO

- Direct Mount Pump

Tie-Downs

- Keyslots: Two at Front, Four at Rear

Winch

- 20,000 lb Worm Gear Winch with 5/8" dia x 75' long cable

Optional Equipment

Deck

- 6" Permanent Steel Tubular Raised Rails
- 6" Removable Steel Tubular Raised Rails
- Steel Rubrail Overlays (1/4" thick x even with deck, 2" above deck, or 4" above deck)
- Outside Stake Pockets with Rubrail - 95" wide deck only
- Outside Stake Pockets with Rubrail and Pipe Spools - 95" wide deck only
- 8" Deep Wheel Wells
- Wheel Well Covers

Headboard

- Stationary Deluxe Headboard with Screen

Lighting

- Emergency Light Package - includes High Output Halogen, Strobe or LED Lightbar, Pair of Work Lights at Rear of Truck and 3 Function Switch Panel
- LED Lighting Package
- Work Lights at Rear of Truck (pair)
- Work Lights at Winch (pair)
- Work Lights on Headboard (pair)
- Various In-Dash and Under-Dash Switch Panels
- Magnetic Tow Light Kit
- Pre-Wiring for Emergency Light Package

Misc.

- Wireless Remote Control for any Operation
- Stainless Steel Wheel Simulators
- Stainless Steel Quarter Fenders
- Jump Start Kit
- 7-Way Trailer Plug with Adapters - pre-wired chassis only
- Air Supply Disconnect at Rear of Truck
- Glad Hands – chassis must have air supply for glad hands
- Locking Chain Racks on Headboard
- Propane Tank Holders with Locking Chain Racks on Headboard
- Folding Three Step Ladder
- Partial Width Forklift Stop
- Duplex Pintle Hitch
- Overcab Protector / Bucket Rest
- "On Demand" Remote Throttle Control - International chassis only

Paint

- Custom Paint Colors Available

PTO

- Air Shift PTO
- Lectra Shift PTO
- Clutch Shift PTO
- Cable Shift PTO
- E-Hydra Shift PTO

Stabilizer

Includes No Lube Pivot Joints and 4-way Receptacle for Auxiliary Tow Lights and Direct Mount Hydraulic Counterbalance Holding Valves, if applicable (stabilizer with tow option only)

- Hydraulic Rear Dock Stabilizer
- Hydraulic Rear Dock Stabilizer with 1,200 lb Capacity 2 1/2" Reese Hitch

- Receiver with 2" Reese Adapter*
- Hydraulic Rear Dock Stabilizer with 5,000 lb Capacity Hydraulic Extend Pintle Hitch Mounting Plate*
- Hydraulic Rear Dock Stabilizer with 5,000 lb Capacity Manual Extend Pintle Hitch Mounting Plate*
- Hydraulic Rear Dock Stabilizer with 4,000 lb Capacity Wheel Lift with Manual L-Arm or T37 Pivoting Wheel Grids

*** - includes 7-way electrical connector at rear of subframe and plug adapters**

Storage

- 36 " long x 18" wide x 18" deep Toolbox with Stainless Steel Door, Full Length Hinge, Beaver Tail Latch, Rubber Mat and Pair of Mounting Brackets
- 48 " long x 18" wide x 18" deep Toolbox with Stainless Steel Door, Full Length Hinge, Beaver Tail Latch, Rubber Mat and Pair of Mounting Brackets
- 60" long x 18" wide x 18" deep Toolbox with Stainless Steel Door, Full Length Hinge, Beaver Tail Latch, Rubber Mat and Pair of Mounting Brackets
- Adjustable Toolbox Shelf
- 29" long x 24" wide x 19" deep Storage Basket with Pair of Mounting Brackets
- 29" long x 15" wide x 19" deep Storage Basket with Pair of Mounting Brackets
- Stainless Steel Cover for Storage Basket
- Door Activated Toolbox Light

Tie-Downs

- Various Assortment of D-Ring Combinations Available
- Various Assortment of Keyslot Combinations Available

Towing

- 3,000 lb Capacity Independent Raise / Lower (IRL) with Hydraulic Extend / Retract and Manual L-Arm or T37 Pivoting Wheel Grids

WHEEL LIFTS: Includes No Lube Pivot Joints, 4-way Receptacle for Auxiliary Tow Lights, Built In Safety Chains with Storage Pockets, Tie-Down Strap Package, Anti-Theft L-Arm Stowage and Direct Mount Hydraulic Counterbalance Holding Valves:

- Ball Hitch Mounting Angle for Wheel Lift
- 500 lb Capacity 2" Reese Hitch Receiver for Wheel Lift

TOWBARS: Includes 4-way Receptacle for Auxiliary Tow Lights, Built-In Safety Chains with Storage Pockets, Tie-Down Chains and Direct Mount Hydraulic Counterbalance Holding Valves, if applicable (IRL only):

- 3,500 lb Capacity Manual Raise / Lower with Hydraulic Extend / Retract and Rubber Tubes

- 3,500 lb Capacity Independent Raise / Lower (IRL) with Hydraulic Extend / Retract and Rubber Tubes or Keyslots

TOW HITCHES: Includes No-Lube Pivot Joints, 4-way Receptacle for Auxiliary Tow Lights and Direct Mount Hydraulic Counterbalance Holding Valves, if applicable (IRL only):

- 3,500 lb Capacity Manual Raise / Lower with Hydraulic Extend / Retract Ball Hitch Mounting Plate*
- 3,500 lb Capacity Manual Raise / Lower with Manual Extend / Retract Ball Hitch Mounting Plate*
- 3,500 lb Capacity Manual Raise / Lower with Hydraulic Extend / Retract Pintle Hitch Mounting Plate*
- 3,500 lb Capacity Manual Raise Lower with Manual Extend / Retract Pintle Hitch Mounting Plate*
- 5,000 lb Capacity Stationary Pintle Hitch Mounting Plate*
- 4,000 lb Capacity Independent Raise / Lower (IRL) with Hydraulic Extend / Retract Manual L-Arm or T37 Pivoting Wheel Grids
- 1,200 lb Capacity 2 1/2" Reese Hitch Receiver with 2" Reese Adapter for 4,000 lb Wheel Lift
- 1,200 lb Capacity Stationary 2 1/2" Reese Hitch Receiver with 2" Reese Adapter*

*** - includes 7-way electrical connector at rear of subframe and plug adapters**

Winch

- Cable Roller Guide
- Cable Tensioner Plate

Specifications

Deck Specifications

Capacity:	30,000 lbs.
Winch:	20,000 lbs.
Width:	95" & 102"
Length:	24', 26' & 28'
Type:	Steel

Required Dimensions Cab to Tandem

24':	134"-146"
26':	158"-170"
28':	182"-196"

Recommended Chassis Requirements

GVWR:	46,000 lbs.
-------	-------------

Rear GVWR:	34,000 lbs.
RBM Total:	3,000,000in-lbs. (both rails combined)
Frame Height:	35"-42"

Patents: 5,782,596 & 5,839,775 and Other Patents Pending