



## **Steel Wrangler 10 Ton**

When you're buying for the big load and the long haul, the Wrangler 10-ton carrier is a good investment. It delivers 20,000 lbs of payload capacity, impressive load angles, and years of reliable use. The Wrangler carrier is available in 24', 26' and 28' decks with or without steel removable rails.

### **Standard Equipment**

#### **Body**

- Dual Lighted Control Stations with Durable Polycarbonate Placards, Polyethylene Hoods and Polished Aluminum Handles
- Reinforced Rigid Tubular Steel Subframe with No Lube Pivot Joints
- No Lube High Performance Replaceable Slide Pad System
- Flexible Nylon Hose / Cable Carrier Tracking System
- Adjustable Tilt Stabilizer Bumpers

#### **Deck**

- 36 KSI, 3/16" Diamond Steel Decking
- W6 x 16 lb/ft Steel Main Deck Beams
- Reinforced Low-Profile Tapered Approach Tip
- Steel Mini-I Beam Crossmembers on 12" Centers
- Steel Angle Flush Style Rubrails with Stake Pockets
- Two Chain and Binder Trays Abreast of Winch
- Heavy Duty Deck Lock / Hold Down System

#### **Headboard**

- Deluxe Bolt-On Steel Headboard with Screen

#### **Hydraulics**

- Dual Hydraulic Counterbalance Locking Valve on Deck Tilt Function
- Abrasion Resistant / Thermal Resistant Hydraulic Hoses

- Hydraulic Reservoir with Integrated Oil Level / Temperature Gauge and Magnetic Clean-Out Provision
- Hydraulic Supply and Return Filtration
- Chrome Plated Cylinder Rods
- System Overload Protection

### **Lighting**

- FMVSS 108 Light Group Utilizing Weather Resistant Harnesses and Connectors

### **Misc.**

- Back-Up Alarm
- Mud Flaps

### **Paint**

- Deck and Subframe Painted Black

### **PTO**

- Direct Mount Pump

### **Tie-Downs**

- Keyslots: Two at Front, Four at Rear

### **Winch**

- 12,000 lb Worm Gear Winch with 7/16" dia x 56' long cable

### **Optional Equipment**

#### **Deck**

- Steel Rubrail Overlays (1/4" thick x even with deck, 2" above deck, or 4" above deck)
- 6" Permanent Steel Tubular Raised Rails
- 6" Removable Steel Tubular Raised Rails
- Outside Stake Pockets with Rubrail - 95" wide deck only
- Outside Stake Pockets with Rubrail and Pipe Spools - 95" wide deck only
- Steel Mini-I Beam Crossmembers on 8" Centers

- 8" Deep Wheel Wells
- Wheel Well Covers

### **Headboard**

- Stationary Deluxe Headboard with Screen

### **Lighting**

- Emergency Light Package - includes High Output Halogen, Strobe or LED Lightbar, Pair of Work Lights at Rear of Truck and 3 Function Switch Panel
- Pre-Wiring for Emergency Light Package
- LED Lighting Package
- Work Lights at Rear of Truck (pair)
- Work Lights at Winch (pair)
- Work Lights on Headboard (pair)
- Various In-Dash and Under-Dash Switch Panels
- Magnetic Tow Light Kit

### **Misc.**

- Wireless Remote Control for any Operation
- Stainless Steel Wheel Simulators
- Stainless Steel Quarter Fenders
- Jump Start Kit
- 7-Way Trailer Plug with Adapters - pre-wired chassis only
- Air Supply Disconnect at Rear of Truck
- "On Demand" Remote Throttle Control - International chassis only
- Locking Chain Racks on Headboard
- Propane Tank Holders with Locking Chain Racks on Headboard
- Folding Three Step Ladder
- Partial Width Forklift Stop - 20,000 lb winch only
- Duplex Pintle Hitch
- Overcab Protector / Bucket Rest
- Glad Hands – chassis must have air supply for glad hands

### **Paint**

- Custom Paint Colors Available

### **PTO**

- Cable Shift PTO
- Air Shift PTO
- E-Hydra Shift PTO
- Lectra Shift PTO

- Clutch Shift PTO

## **Stabilizer**

**Includes No Lube Pivot Joints and 4-way Receptacle for Auxiliary Tow Lights and Direct Mount Hydraulic Counterbalance Holding Valves, if applicable (stabilizer with tow option only)**

- Hydraulic Rear Dock Stabilizer
- Hydraulic Rear Dock Stabilizer with 1,200 lb Capacity 2 1/2" Reese Hitch Receiver with 2" Reese Adapter\*
- Hydraulic Rear Dock Stabilizer with 5,000 lb Capacity Hydraulic Extend Pintle Hitch Mounting Plate\*
- Hydraulic Rear Dock Stabilizer with 5,000 lb Capacity Manual Extend Pintle Hitch Mounting Plate\*
- Hydraulic Rear Dock Stabilizer with 4,000 lb Capacity Wheel Lift with Manual L-Arm or T37 Pivoting Wheel Grids

**\* - includes 7-way electrical connector at rear of subframe and plug adapters**

## **Storage**

- 36 " long x 18" wide x 18" deep Toolbox with Stainless Steel Door, Full Length Hinge, Beaver Tail Latch, Rubber Mat and Pair of Mounting Brackets
- 48 " long x 18" wide x 18" deep Toolbox with Stainless Steel Door, Full Length Hinge, Beaver Tail Latch, Rubber Mat and Pair of Mounting Brackets
- 60" long x 18" wide x 18" deep Toolbox with Stainless Steel Door, Full Length Hinge, Beaver Tail Latch, Rubber Mat and Pair of Mounting Brackets
- Adjustable Toolbox Shelf
- Door Activated Toolbox Light
- 29" long x 24" wide x 19" deep Storage Basket with Pair of Mounting Brackets
- 29" long x 15" wide x 19" deep Storage Basket with Pair of Mounting Brackets
- Stainless Steel Cover for Storage Basket

## **Tie-Downs**

- Various Assortment of D-Ring Combinations Available
- Various Assortment of Keyslot Combinations Available

## **Towing**

**WHEEL LIFTS: Includes No Lube Pivot Joints, 4-way Receptacle for Auxiliary Tow Lights, Built In Safety Chains with Storage Pockets, Tie-Down Strap Package, Anti-Theft L-Arm Stowage and Direct Mount Hydraulic Counterbalance Holding Valves:**

- 3,000 lb Capacity Independent Raise / Lower (IRL) with Hydraulic Extend /

- Retract and Manual L-Arm or T37 Pivoting Wheel Grids
- 4,000 lb Capacity Independent Raise / Lower (IRL) with Hydraulic Extend / Retract Manual L-Arm or T37 Pivoting Wheel Grids
- Ball Hitch Mounting Angle for Wheel Lift
- 500 lb Capacity 2" Reese Hitch Receiver for Wheel Lift
- 1,200 lb Capacity 2 1/2" Reese Hitch Receiver with 2" Reese Adapter for 4,000 lb Wheel Lift

**TOWBARS: Includes 4-way Receptacle for Auxiliary Tow Lights, Built-In Safety Chains with Storage Pockets, Tie-Down Chains and Direct Mount Hydraulic Counterbalance Holding Valves, if applicable (IRL only):**

- 3,500 lb Capacity Manual Raise / Lower with Hydraulic Extend / Retract and Rubber Tubes
- 3,500 lb Capacity Independent Raise / Lower (IRL) with Hydraulic Extend / Retract and Rubber Tubes or Keyslots

**TOW HITCHES: Includes No-Lube Pivot Joints, 4-way Receptacle for Auxiliary Tow Lights and Direct Mount Hydraulic Counterbalance Holding Valves, if applicable (IRL only):**

- 3,500 lb Capacity Manual Raise / Lower with Hydraulic Extend / Retract Ball Hitch Mounting Plate\*
- 3,500 lb Capacity Manual Raise / Lower with Manual Extend / Retract Ball Hitch Mounting Plate\*
- 3,500 lb Capacity Manual Raise / Lower with Hydraulic Extend / Retract Pintle Hitch Mounting Plate\*
- 3,500 lb Capacity Manual Raise Lower with Manual Extend / Retract Pintle Hitch Mounting Plate\*
- 1,200 lb Capacity Stationary 2 1/2" Reese Hitch Receiver with 2" Reese Adapter\*
- 5,000 lb Capacity Stationary Pintle Hitch Mounting Plate\*

**\* - includes 7-way electrical connector at rear of subframe and plug adapters**

**Winch**

- Remote Free Spool Release - 12,000 lb winch only
- Combination Cable Roller Guide / Tensioner Plate - 12,000 lb winch only
- 20,000 lb Worm Gear Winch with Remote Air Free Spool Release and 5/8" dia x 75' long cable
- Cable Roller Guide - 20,000 lb winch only
- Cable Tensioner Plate - 20,000 lb winch only

**Specifications**

**Deck Specifications**

|           |             |
|-----------|-------------|
| Capacity: | 20,000 lbs. |
| Winch:    | 12,000 lbs. |

Width: 96" & 102"  
Length: 24', 26' & 28'  
Type: Steel

**Required Dimensions Cab to Axle**

24': 156"-168"  
26': 180"-192"  
28': 204"-218"

**Required Dimensions Cab to Tandem**

24': 134"-146"  
26': 158"-170"  
28': 182"-196"

**Recommended Chassis Requirements**

GVWR: 33,000 lbs.  
Rear GVWR: 20,000 lbs.  
RBM Total: 2,000,000in-lbs. (both rails combined)  
Frame Height: 35"-42"

**Patents: 5,782,596 & 5,839,775 and Other Patents Pending**